

# HAFFMANS c-DGM CO<sub>2</sub>/O<sub>2</sub> GEHALTEMETER

PRODUCT LEAFLET

## GENERAL PRODUCT INFORMATION

In the beer and beverage industries, the content of dissolved carbon dioxide (CO<sub>2</sub>) and oxygen (O<sub>2</sub>) are determining factors in the quality, taste and flavor stability of beer and carbonated beverages. Particularly, O<sub>2</sub> is an important parameter as it causes a rapid decline of the flavor stability and shelf life. Because of this, breweries, as well as soft drink manufacturers continuously control and measure the concentrations of CO<sub>2</sub> and O<sub>2</sub> during production.

The CO<sub>2</sub>/O<sub>2</sub> Gehaltemeter, type c-DGM, combines the internationally accepted determination of the dissolved CO<sub>2</sub> content based on Henry's Law with a highly accurate dissolved O<sub>2</sub> measurement. This state-of-the-art optical O<sub>2</sub> measurement technology is greatly improved compared to the traditional O<sub>2</sub> measuring instruments and doesn't require frequent calibration. Its design allows for higher product pressure, making it suitable for the soft drink industry. Up to 10 different product types can be programmed into the c-DGM. An advanced operator and location identification system allows for the traceability of measuring data. The optional bumper protects the instrument against physical impact in harsh environments.

After operator/location identification, sampling takes place. When the CO<sub>2</sub> measurement is started, the O<sub>2</sub> content is stored. Automatically, equilibrium is created, followed by the measurement of pressure and temperature. The dissolved CO<sub>2</sub> content is then electronically calculated and displayed. The data can be securely transferred to a PC using the interface cable.

Besides the combined CO<sub>2</sub>/O<sub>2</sub> measurement, the c-DGM is suitable for single O<sub>2</sub> measurement, continuous O<sub>2</sub> measurement and single CO<sub>2</sub> measurement.

## BENEFITS

- Accurate product control
  - reproducible and operator independent results
- Cost saving
  - lower investment costs (one device for CO<sub>2</sub> and O<sub>2</sub> measurement and up to 10 product types)
  - less labor intensive
  - reduction of beer loss
  - low maintenance

## APPLICATIONS

- At-line, sampled directly during the production process (from process lines, vessels, tanks or kegs)
- Laboratory, after the production, sampled from a variety of bottles or cans



# HAFFMANS c-DGM CO<sub>2</sub>/O<sub>2</sub> GEHALTEMETER

PRODUCT LEAFLET

## TECHNICAL DATA

### O<sub>2</sub> content

Measuring range 0.0 - 2,000 ppb  
Accuracy ± 1 ppb + 2 % of m.v.\*  
Measuring Units ppb, µg/l, ppm, mg/l, %

### CO<sub>2</sub> content

Measuring range 2.0 - 10.0 g/l  
Accuracy ± 0.05 g/l  
Measuring Units g/l, % b.w., Vol, kPa

### Temperature

-5.0 - 40.0 °C, acc. ± 0.2 °C

### Pressure

0.0 - 10.0 barg, acc. ± 0.01 bar

### Measuring time incl sampling

Approx. 120 sec.

### Number of measurements per charge

Approx. 120

### Interface

RS-232

### Dimensions

210 x 130 x 260 (LxWxH mm)

### Weight

ca. 3.2 kg

\* at 20 °C

## SCOPE OF SUPPLY

- CO<sub>2</sub>/O<sub>2</sub> Gehaltemeter, type c-DGM
- Service set with power supply (Euro or US plug)
- Software set (CD + Interface cable)
- Set of two sample hoses
- Operator ID - key (2 pieces)
- Location ID - key (2 pieces)
- Instruction manual

## OPTIONS

- Certificate of measurement
- Bumper
- Quick charger
- Inpack 2000 Sampling Device "special"



Optional bumper



### HAFFMANS BV

P.O. BOX 3150 NL-5902 RD VENLO, NETHERLANDS WWW.HAFFMANS.NL

All Pentair trademarks and logos are owned by Pentair, Inc. All other brand or product names are trademarks or registered marks of their respective owners. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice.

Pentair is an equal opportunity employer.

c-DGM E-4 /12 © 2012 Pentair, Inc. All Rights Reserved.

